

QUICK NOTES

SINOPEC 2-WELL ELMWORTH MONTNEY PAD

In September 2021 Sinopec Daylight Energy Ltd. completed a two-well pad in the Montney formation in Alberta, Canada. As single point entry multistage lateral completions have proven to be successful in the area, the Stage Completions Bowhead system was used in both wellbores.

BOWHEAD SYSTEM

BY THE NUMBERS

110

Bowhead Valves



100%

Valve-Opening Rate

14.5 million lbs
of Proppant Pumped



Maximum Flow Rate of

63 bpm

DESIGN DETAILS

The completion plans for the **18,400 ft** of combined lateral included **63-bpm slickwater fracs** with **~ 130-170 ft stage spacing**. Proppant was designed at **800 lb/ft** at a maximum concentration of **160 lb/bbl**.

55 Bowhead valves and one toe port were installed in each 4 ½" liner, totalling **112 stages** for the pad.

JOB EXECUTION

The Bowhead valves operated without incident and were deemed an operational success allowing the fracs to be executed as planned. 55 individually profiled collets and dissolvable balls were launched in each well (between fracs) and successfully opened each corresponding valve.

Both wells were fraced in under 8 days, including time between wells. Crews were able to reach an **average pump time efficiency of 20.6 hours per day**.

BOWHEAD is a multistage single point entry frac system offering a near limitless number of fracs per well. Cemented or uncemented, this system allows operators to target optimal spacing and distribution while providing unprecedented confidence in valve-opening accuracy.

01

Single Point Entry

A cementable multi-stage single point entry frac valve system offering near limitless fracs.

02

Continual Pumping

Individually profiled collets pumped with dissolvable balls result in continual pumping.

03

Safer, Smaller

Large-bore, fluid-conveyed collets eliminate the need for wireline, coiled tubing and perforating guns at the wellsite.

